

HF Adapter

Mechanik
Anschlüsse: BNC-Kupplung > Cinch-Stecker
Gewicht: 7 g

Elektrik
Testspannung: 2000 V~ 1 Min.
Isolationswiderstand: 1000 MΩ/Min. @ 500 V
Kontaktwiderstand: 15 MΩ max.
Impedanz: 50 Ω

Material
Kontakt: Messing; vergoldet
Gehäuse: Messing; vernickelt
Dielektrikum: Teflon; weiß

RoHS-konform

HF Adapter


Mechanical
Connectors: BNC jack > RCA plug
Weight: 7 g

Elektrical
Test voltage: 2000 V~ 1 Min.
Insulation resistance: 1000 MΩ/Min. @ 500 V
Contact resistance: 15 MΩ max.
Impedance: 50 Ω

Material
Contact: Brass; gold-plated
Housing: Brass; nickel-plated
Dielectric: Teflon; white

RoHS compliant

Änderungen

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.: 24.02.2015	tf	NC 1524 RCA M - BNC F	
		gepr.: 24.02.2015	tf		
		Norm:		Zeichnungs-Nr.: 11355	von
Änderungen vorbehalten / Subject to change					