



Art.-Nr. / Item No.	Beschreibung / Description	Länge / Length (L)
74760	DP 2.1 Kabel STD 0100 1,0m sw 80GB	1000 ± 20 mm



DisplayPort™ Verbindungskabel 2.1

- hochauflösende UHD-Signalübertragung mit bis zu 16K @ 60 Hz
- max. Datenübertragungsrate von bis zu 80 Gbit/s
- mit Staubschutzkappe

Anschlüsse:	2x DisplayPort™-Stecker
Kontakte:	vergoldet
Kabeltyp:	Rundkabel
Material Kabelmantel:	PVC, schwarz
Außendurchmesser Kabel:	6,3 ± 0,2 mm
Max. Datenübertragungsrate:	80 Gbit/s
Unterstützte Videostandards:	16K @ 60 Hz (15360 x 8640) 8K @ 60 Hz (7680 x 4320) 4K @ 144 Hz (3840 x 2160)
Isolationswiderstand:	300 V $\overline{=}$, 10 M Ω min.
Betriebstemperatur:	-10°C - +60°C
Lagertemperatur:	-20°C - +80°C

DisplayPort™ Connector Cable 2.1

- High-resolution signal transmission with up to 16K @ 60 Hz
- max. data transmission rate of up to 80 Gbit/s
- with protective dust cap

Connections:	2x DisplayPort™ plug
Contacts:	gold-plated
Cable type:	round cable
Material Cable Jacket:	PVC, black
Outer diameter cable jacket:	6.3 ± 0.2 mm
Max. Data transmission rate:	80 Gbit/s
Supported video standards:	16K @ 60 Hz (15360 x 8640) 8K @ 60 Hz (7680 x 4320) 4K @ 144 Hz (3840 x 2160)
Insulation resistance:	300 V $\overline{=}$, 10 M Ω min.
Operating temperature:	-10°C - +60°C
Storage temperature:	-20°C - +80°C

Änderungen

Datum	Name	gez.:	Datum	Name	Bezeichnung	Blatt
		gez.:	23.09.2024	alw	DP 2.1 Kabel STD XXXX 1,0m sw 80GB	1/1
		gepr.:	23.09.2024	alw		
		Norm:			Zeichnungs-Nr.:	von
Änderungen vorbehalten / Subject to change					74760	

